

Vibration Isolation Pads



These ultra durable neoprene pads can be used to effectively control noise and vibration, particularly in applications involving power generation equipment. These pads are available in a multitude of sizes to meet the needs of almost any installation application. They have a smooth pattern on both sides and are colored black.

Features

- ▶ 60 durometer neoprene
- ▶ Solid construction (unlike waffle pads) offers higher loading per square inch
- ▶ Max loading: 1015 PSI
- ▶ Sizes to fit almost any application
- ▶ 1/4" thickness
- ▶ Aids in sound dampening by reducing high frequency noise
- ▶ Easily cut to any desired shape
- ▶ Can be used in multiple layers to increase deflection
- ▶ Chemical and oil resistant
- ▶ -40°F to 194°F temperature range



Specifications

Pad Size (inches)	Part #	Max Load Per Pad	Mounting Hole Size
2 x 4 x 1/4	10155	8120 lbs.	9/16"
2 x 6 x 1/4	10156	12180 lbs.	11/16"
2 x 8 x 1/4	10157	16240 lbs.	13/16"
3 x 8 x 1/4	10158	24360 lbs.	13/16"
2 1/2 x 10 x 1/4	10159	25375 lbs.	13/16"
3 x 12 x 1/4	10160	36540 lbs.	13/16"